

MATERIAL SAFETY DATA SHEET

Bronc Max

I. NAME

PRODUCT/TRADE NAME: BRONC MAX
EPA REGISTRATION #: NONE
CHEMICAL NAME/COMMON NAME:
Ammonium Sulfate/Ammonium Sulfate
Polydimethylsiloxane/Silicone

II. HAZARDOUS INGREDIENTS

	CAS#	OSHA PEL	ACGIH TLV
Ammonium Sulfate	7783-20-2	NE	NE
Silicone	70131-67-8	NE	NE

III. PHYSICAL DATA

SPECIFIC GRAVITY (H₂O = 1): 1.23
MELTING POINT: NA
VAPOR DENSITY (AIR = 1): NE
% VOLATILES BY VOL.: NE
ODOR: Apple
APPEARANCE: Light Green Liquid
FLASH POINT/METHOD: NA
VAPOR PRESSURE (mmHg): NA
SOLUBILITY IN H₂O: Soluble

IV. FIRE & EXPLOSION HAZARD

EXTINGUISHING MEDIA: ☒ Water Fog ☐ Foam ☐ Alcohol Foam
☐ CO₂ ☐ Dry Chemical ☐ Other

FIRE FIGHTING PRECAUTIONS & HAZARDS:

Fight fire upwind. Wear positive pressure self-contained breathing apparatus and full protective equipment. Do not breathe smoke or spray mist. Avoid fallout and runoff. Dike to prevent entering drains, sewers, or water courses. Evacuate people downwind from fire.

V. CARCINOGEN STATUS

☐ OSHA ☐ NTP ☐ IARC ☒ No Listing Type

VI. REACTIVITY

☒ Stable HAZARDOUS POLYMERIZATION
☐ Unstable ☐ May Occur ☒ Will Not Occur
AVOID: Bases, Oxidizers, Potassium Chlorate, Potassium Nitrate, Chlorine, Hypochlorates
HAZARDOUS DECOMPOSITION PRODUCTS: CO_x, SO_x

VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE OF SPILL: Absorb with inert material and sweep or vacuum into disposal container.
DECONTAMINATION: Treat spill area with detergent and water. Repeat as necessary until area is clean.
ENVIRONMENTAL HAZARDS: May be toxic to aquatic organisms. Dike to prevent entering drains, sewers or water courses.
DISPOSAL: Dispose of in accordance with Federal, State and local regulations.

VIII. HEALTH PRECAUTION DATA

INGESTION: Acute oral LD₅₀ (rat) 5000 mg/kg (RTECS*). Do not ingest. Wash thoroughly before eating, drinking or smoking.
INHALATION: No PEL/TLV established for this product. Wear proper respiratory protection for exposures encountered. May be irritating to the respiratory tract.
SKIN ABSORPTION: Acute dermal LD₅₀ (rabbit) 3 g/kg (Chevron). Can cause skin irritation. Wear proper personal protective equipment to reduce skin exposure.
EYE EXPOSURE: Keep out of eyes. May cause eye irritation. If exposed, flush eyes for a minimum of 15 minutes with water. Wear proper eye protection to reduce exposure.
EFFECTS OF OVEREXPOSURE: Can cause respiratory tract and eye irritation. Ingestion could cause corrosive deterioration of digestive system tissue and ingestion of large amounts may result in vomiting and diarrhea and excessive fluid loss. No known chronic effects. Preexisting medical conditions involving the above symptoms may be aggravated by exposure.
FIRST AID: In all cases, get prompt medical attention. If ingested, give several glasses of water and induce vomiting. Do not induce vomiting if person is unconscious.

For skin exposure, remove contaminated clothing and wash with soap and water. For eye exposure, irrigate for a minimum of 15 minutes with water. If inhaled, remove victim to fresh air, and administer CPR if necessary.

IX. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear only NIOSH/MSHA - approved respiratory protection for the exposures encountered. Positive pressure self-contained breathing apparatus should be used for confined space entry and high exposure operations.
PERSONAL PROTECTIVE EQUIPMENT: Work gloves, safety goggles or glasses with side shields and brow protection.
VENTILATION: General ventilation should be sufficient for intended use.

X. SPECIAL PRECAUTIONS

Keep out of the reach of children. Read and follow all label instructions. May be corrosive to copper, brass, steel, aluminum and concrete.

XI. REGULATORY DATA

SARA HAZARD CLASS: ☒ Acute ☐ Chronic ☐ Flammable
☐ Pressure ☐ Reactive ☐ None

SARA 313: ☐ Yes ☒ No Chemical:

SARA 302: ☐ Yes ☒ No Chemical:

TPQ:

CERCLA: ☐ Yes ☒ No Chemical:

RQ:

RCRA: ☐ Yes ☒ No

NFPA HAZARD RATING:

Health: [1]
Fire: [1]
Reactivity: [0]
Special: []

HMIS CODES:

Health: [1]
Fire: [1]
Reactivity: [0]

NFPA HAZARD RATING SCALE:

0 = Minimal 3 = Serious
1 = Slight 4 = Severe
2 = Moderate

HMIS HAZARD RATING SCALE:

0 = Minimal 3 = Serious
1 = Slight 4 = Severe
2 = Moderate

DATE PREPARED: March 27, 2001

REVISED DATE: April 2, 2010

Notice: This information was developed from information on the constituent materials. No warranty is expressed or implied regarding the completeness or continuing accuracy of the information contained herein, and Wilbur-Ellis disclaims all liability for reliance thereon. The user should satisfy himself that he has all current data relevant to his particular use.

*Technical Material NE - Not Established NA - Not Applicable

24 Hour Emergency Phone Number
CHEMTREC: (800) 424-9300

