

MATERIAL SAFETY DATA SHEET

R-11

I. NAME

PRODUCT/TRADE NAME: R-11

EPA REGISTRATION #: NONE

CHEMICAL NAME/COMMON NAME:

1-Butanol/Butyl Alcohol

Polyoxyethylene Nonyl Phenol [-p-Nonylphenyl]-v-hydroxypoly-(oxyethylene)/Nonionic Surfactants

II. HAZARDOUS INGREDIENTS

	CAS#	OSHA PEL	ACGIH TLV
Butyl Alcohol	71-36-3	50ppm c	50ppm c
Nonionic Surfactants	9016-45-9	NE	NE

III. PHYSICAL DATA

SPECIFIC GRAVITY (H₂O = 1): 1.02

MELTING POINT: NA

VAPOR DENSITY (AIR = 1): NE

% VOLATILES BY VOL.: NE

ODOR: Alcohol

APPEARANCE: Clear Liquid

FLASH POINT/METHOD: 130 Deg. F TCC

VAPOR PRESSURE (mmHg): NE

SOLUBILITY IN H₂O: 10%

IV. FIRE & EXPLOSION HAZARD

EXTINGUISHING MEDIA: ☒ Water Fog ☒ Foam ☐ Alcohol Foam
☒ CO₂ ☒ Dry Chemical ☐ Other

FIRE FIGHTING PRECAUTIONS & HAZARDS:

Fight fire upwind. Wear positive pressure self-contained breathing apparatus and full personal protective equipment. Cool exposed containers with water. Dike area to prevent entering drains, sewers or water courses. Evacuate people downwind from fire.

V. CARCINOGEN STATUS

☐ OSHA ☐ NTP ☐ IARC ☒ No Listing Type

VI. REACTIVITY

☒ Stable HAZARDOUS POLYMERIZATION

☐ Unstable ☐ May Occur ☒ Will Not Occur

AVOID: Oxidizers, Liquid chlorine and Concentrated O₂

HAZARDOUS DECOMPOSITION PRODUCTS: CO_x

VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE OF SPILL: Wear appropriate respiratory and personal protective equipment. Absorb with inert material and sweep or vacuum into approved disposal container.

DECONTAMINATION: Treat area with detergent and water. Absorb with inert material and place in approved container. Repeat as necessary until area is clean.

ENVIRONMENTAL HAZARDS: Dike to prevent entering drains, sewers or water courses.

DISPOSAL: Place in DOT-approved container and dispose of in an approved disposal site.

VIII. HEALTH PRECAUTION DATA

INGESTION: Acute oral LD₅₀ (rat) Butyl Alcohol 790 mg/kg (SAX*). Wash thoroughly before eating, drinking or smoking. Do not ingest. Do not store near food or feed.

INHALATION: PEL/TLV Butyl Alcohol 100 ppm. Can cause respiratory irritation in high concentrations. Wear appropriate respiratory protection for exposures above the PEL/TLV.

SKIN ABSORPTION: Acute dermal LD₅₀ (rabbit) for Butyl Alcohol 4200 mg/kg (SAX*). Can cause mild skin irritation or dermatitis. Wear proper personal protective equipment to reduce exposure.

EYE EXPOSURE: May be mildly irritating to the eyes. If exposed, flush eyes a minimum of 15 minutes with water. Wear proper eye protection to reduce splash exposure.

EFFECTS OF OVEREXPOSURE: May cause eye irritation and corneal inflammation.

High concentrations can cause respiratory irritation. May cause skin irritation, scaling or dermatitis. No known chronic effects. Preexisting medical conditions involving the above symptoms may be aggravated by exposure.

FIRST AID: In all cases, get prompt medical attention. If ingested, give several glasses of water. Do not induce vomiting. For skin exposure, remove contaminated clothing and wash with soap and water. For eye contact, irrigate eyes a minimum of 15 minutes with water. For inhalation, remove victim to fresh air, and administer CPR if necessary.

IX. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Use only NIOSH/MSHA - approved respiratory protection for organic vapors up to 10 times the PEL/TLV. Positive pressure self-contained breathing apparatus should be used for confined space entry and high exposures above 10 times the PEL/TLV.

PERSONAL PROTECTIVE EQUIPMENT: Not normally required for this product. Recommend chemical goggles, long-sleeved coveralls and rubber or neoprene boots, Nitrile gloves.

VENTILATION: Local exhaust ventilation recommended for manufacture and formulation operations.

X. SPECIAL PRECAUTIONS

Keep out of the reach of children. Read and follow all label instructions. Keep away from open flame, heat or ignition sources.

XI. REGULATORY DATA

SARA HAZARD CLASS: ☐ Acute ☐ Chronic ☒ Flammable
☐ Pressure ☐ Reactive ☐ None

SARA 313: ☒ Yes ☐ No Chemical: Butyl Alcohol

SARA 302: ☐ Yes ☒ No Chemical:

TPQ:

CERCLA: ☒ Yes ☐ No Chemical: Butyl Alcohol

RQ: 1*

RCRA: ☒ Yes ☐ No

NFPA HAZARD RATING:

Health: [1]

Fire: [2]

Reactivity: [0]

Special: [0]

HMIS CODES:

Health: [1]

Fire: [2]

Reactivity: [0]

NFPA HAZARD RATING SCALE:

0 = Minimal 3 = Serious

1 = Slight 4 = Severe

2 = Moderate

HMIS HAZARD RATING SCALE:

0 = Minimal 3 = Serious

1 = Slight 4 = Severe

2 = Moderate

DATE PREPARED: May 8, 1985

REVISED DATE: May 14, 2010

Notice: This information was developed from information on the constituent materials. No warranty is expressed or implied regarding the completeness or continuing accuracy of the information contained herein, and Wilbur-Ellis disclaims all liability for reliance thereon. The user should satisfy himself that he has all current data relevant to his particular use.

*Technical Material NE - Not Established NA - Not Applicable

24 Hour Emergency Phone Number
CHEMTREC: (800) 424-9300



PO BOX 1286 • FRESNO CA 93715

WECO MSDS\WR11.p65