

Tri-Clor Fumigant

1. IDENTIFICATION

PRODUCT IDENTIFIER: Tri-Clor Fumigant Date: February 19, 2015
OTHER MEANS OF IDENTIFICATION: Chloropicrin, Trichloronitromethane SDS No.: 100-USA-TCI

RECOMMENDED USE: Pesticide (Fumigant), Warning agent

Distributor:

Trical, Inc. 8770 Highway 25 Hollister, CA 95023

Business Number: (831) 637-0195

E-mail: sds@trical.com

FOR CHEMICAL EMERGENCY

(Spill, Leak, Fire, Exposure, or Accident),

Call CHEMTREC:

(800) 424-9300 (24 hours) (703) 527-3887 (if outside USA)

NOTE TO PESTICIDE HANDLERS: If the pesticide product end-use labeling contains specific instructions or requirements that conflict with this Safety Data Sheet (SDS), **follow the instructions or requirements on the labeling**. See Section 15 of this SDS for further information.

2. HAZARDS IDENTIFICATION

GHS Classification	Acute Toxicity, Category 1 (inhalation)
Of 10 Olassinoation	Acute Toxicity, Category 2 (oral)
	Acute Toxicity, Category 2 (dermal)
	Skin Corrosion/Irritation (1C) (liquid contact)
	Eye Damage/Irritation – Category 1 (liquid contact)
	Eye Irritation, Category 2A (vapor contact)
	Specific Target Organ Toxicity, Single Exposure, Category 1 (respiratory)
	Specific Target Organ Toxicity, Repeat Exposure, Category 1 (respiratory)
	Aquatic Toxicity Acute, Category 1









Signal Word	DANGER	
GHS	 Fatal if inhaled, swallowed, or in contact with skin. H330+H300+H310 Causes severe skin burns and eye damage (liquid contact). H314 	
Hazard Statements	• Causes serious eye irritation (vapor contact). H319	
	 Causes damage to the respiratory tract and to lungs from single exposure or through prolonged or repeated exposure by inhalation. H370+H372 	
	• Very toxic to aquatic life. H400	



Tri-Clor Fumigant

GHS PRECAUTIONARY STATEMENTS

Prevention

- Do not breathe gas or vapors. P260
- Do not get in eyes, on skin, or on clothing. P262
- Wear respiratory, eye, hand, and skin protection in accordance with the product label. P284+P280
- Use only outdoors or in a well-ventilated area. P271
- Do not eat, drink, or smoke when using this product. P270
- Wash hands thoroughly after handling. P264
- Keep away from heat/sparks/open flames/hot surfaces No Smoking. P210
- Store away from combustible materials. P220
- Avoid release to the environment. P273

Response

- IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a physician or poison control center. P304
- IF IN EYES: Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing eyes. Immediately call a physician or poison control center if liquid contact. For vapor contact, if eye irritation persists, get medical advice or attention. P305
- IF ON SKIN: Take off contaminated clothing immediately. Wash with plenty of water and soap. Immediately call a physician or poison control center. P302+P361+P352+P310
- IF SWALLOWED, immediately call a physician or poison control center. Rinse mouth. Do NOT induce vomiting. P310+P330+P331
- Get medical advice if you feel unwell or if eye irritation persists. P314+P337
- Wash contaminated clothing before reuse. P363:
- In case of fire, evacuate area. Fight fire remotely due to the risk of cylinder rupture. Use water, dry chemical, or any other conventional media. P370+P380+P375+P378:

Storage

- Protect from sunlight, store in well-ventilated place away from other materials, store locked up, keep container or cylinder valve tightly closed. P410+P403+P405+P233
- Store at temperatures not exceeding 55 °C (131 °F). P411

Disposal

- Collect spillage. P391
- Dispose of contents and container in accordance with government regulations. (See Section 13). P501

Hazards Not Otherwise Classified

- Lachrymator Vapor extremely irritating to the eyes and respiratory tract.
- Closed cylinders may rupture or burst if heated by fire.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Identity	Synonyms	CAS #	Concentration
Chloropicrin	Trichloronitromethane	76-06-2	99.0%*
Impurities			Balance**

^{*} Mactive ingredient nominal. For reporting imports and exports pursuant to Chemical Weapons Convention, use 100% Chloropicrin.

^{**} The impurities do not contribute to the classification of this product.



Tri-Clor Fumigant

4. FIRST AID MEASURES

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Qualified persons should administer oxygen, if available. If breathing has stopped, give artificial respiration. Use a pocket mask equipped with a one-way valve or other proper respiratory medical device. Do not use mouth-to-mouth method if victim inhaled chloropicrin. Symptoms of lung edema (shortness of breath) may develop up to 24 hours after exposure. Immediately call an ambulance if any breathing difficulty persists after removal from exposure area. Call a physician or poison control center for further treatment advice.
Eyes	Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes; then continue rinsing eyes. Immediately call a physician or poison control center if liquid contact occurs. For vapor contact, if eye irritation persists, get medical advice or attention.
Skin	Remove and isolate contaminated clothing and shoes, and other items covering the skin. Rinse skin immediately with plenty of water for 15-20 minutes. Call a physician or Poison Control Center immediately. Aerate and then wash any contaminated clothing or shoes separately before reuse. Dispose of heavily contaminated clothing and shoes.
Ingestion	IF SWALLOWED: Immediately call a Poison Control Center or physician. Have victim rinse mouth thoroughly with water. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from Poison Control Center or physician. If vomiting occurs, keep head low to minimize aspiration of stomach contents.
Most Important Symptoms/Effects, Acute and Delayed	Chloropicrin is a volatile liquid and a potent lachrymator (eye tearing). Early symptoms of overexposure are lachrymation, respiratory distress, and vomiting. Pulmonary edema and pulmonary symptoms may be delayed. Treat symptomatically.
Indication of Immediate Medical Attention or Special Treatment.	Obtain medical assistance at once in case of illness or burn after exposure, or if irritation to eyes and respiratory tract persist. Do not allow conditions that could cause further exposure until recovery is complete.
General Advice	Ensure that medical personnel are aware of the material involved, and that they take precautions to protect themselves from exposure to chloropicrin vapor from victim's clothing or stomach contents. At lower concentrations (73-150 ppb), chloropicrin behaves as mild sensory irritant. At concentrations above 150 ppb, cough, headache, nausea, and vomiting may occur. These symptoms are temporary and reversible following termination of exposure. See Section 11 Toxicology Section for more information.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing	All conventional fire extinguishing media are suitable: water spray, dry chemical,
Media	carbon dioxide, alcohol-resistant foam.
Unsuitable Extinguishing Media	None



Tri-Clor Fumigant

Specific Hazards Arising from the Chemical including Hazardous Combustion Products	 Non-combustible. Substance itself does not burn but may decompose upon heating to produce corrosive, toxic, and/or irritating gases or vapors. Vapors are not explosive. Vapors are heavier than air. They can spread along the ground and collect in low or confined areas. Closed cylinders may rupture or burst if heated by fire. Rapid decomposition may burst closed containers under fire conditions. NOTE: Cylinders containing Chloropicrin are not equipped with relief valves or fusible overpressure devices.
Hazardous Combustion Products	Carbon monoxide, chlorine, hydrogen chloride, phosgene, nitrosyl chloride, and nitrogen oxides.
Special Protective Equipment	Wear self-contained breathing apparatus and full turnout gear for fire situations.
Precautions for Fire Fighters	 Stay upwind. DO NOT approach containers suspected to be hot. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Evacuate area at least 150 meters (500 feet), initially. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. Move containers from fire area if you can do it without risk. Cool containers with flooding quantities of water until well after fire is out. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures	 Use proper personal protective equipment (PPE) as indicated in Section 8. Do not touch damaged containers or spilled material unless wearing appropriate PPE. Avoid breathing vapors and contact with skin and eyes. Keep unnecessary personnel away. Avoid low places, ventilate closed spaces before entering, and work upwind if possible. Do not permit entry into the spill or leak area by any person not wearing proper PPE until Chloropicrin is measured to be less than 0.15 ppm. After clean-up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
Environmental	• Prevent entry into waterways, sewers, basements, or confined areas.
Precautions	• Contact local authorities in case of spillage to drain/aquatic environment.
Methods and Materials for	• Stop leak if you can do so without risk.
Containment	• Dike the spilled material where possible with sand, earth, or vermiculite.



Tri-Clor Fumigant

Methods for Cleaning Up Small Liquid Spills 55 gallons or less	 Isolate immediate area at least 100 feet (30 m), initially. Wear recommended PPE. Chloropicrin readily vaporizes so ensure area is well-ventilated. Move leaking or damaged cylinders outdoors to an isolated location, if safe to do so. Position cylinder or other packaging to minimize potential for liquid to leak out. Allow spilled fumigant to evaporate or cover spill with water, soil, or plastic tarp to reduce vapors. Absorb onto inert material such as vermiculite, dry sand, or dirt, and deposit spill into a sealable polyethylene or steel container that is labeled appropriately. Ventilate area before allowing re-entry and until the concentration of Chloropicrin is measured to be less than 0.15 ppm.
Methods for Cleaning Up Large Liquid Spills > 55 gallons	 Isolate at least 500 feet (150 m) in all directions, initially. Wear self-contained breathing apparatus (SCBA) and recommended PPE (see Section 8) Contain with dike and cover diked area with plastic sheeting or with water to reduce vapors.
Other Information	• For disposal, see Section 13.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

This product is a highly hazardous material and must be handled with care only by certified pesticide applicators or persons under their direct supervision who are trained with its proper use. IF THE INFORMATION IN THIS SDS DIFFERS FROM THAT ON THE END USE LABELING FOR THIS PRODUCT, THE HANDLER MUST FOLLOW THE PRECAUTIONARY STATEMENTS ON THE END USE LABELING (See Section 15, FIFRA).

- Wear PPE in accordance with Section 8. Leather or other abrasion resistant gloves can be worn when handling or moving closed and capped cylinders.
- Wash hands and face before eating, drinking, or smoking after handling material. Handle in accordance with good industrial hygiene and safety practice.
- Do not drop, drag, slide or roll cylinders on their sides.
- Ropes, slings, hooks, tongs, and similar handling devices should not be used for unloading cylinders. A
 suitable hand truck, fork truck, or similar device to which the cylinders can be firmly secured should be used
 for transporting the heavier cylinders.
- Keep valves closed and secured with the valve cap, when the cylinder is not in use or is empty. Only hand-tighten valves and caps. Leaving an empty cylinder valve open can introduce moisture and thereby increase the potential for internal corrosion.
- Use an adjustable strap wrench to remove caps that are over-tightened or rusted. Never insert an object (e.g. wrench, screw driver) into cap openings.
- Ventilation: When possible, open cylinder (slowly) only in a well-ventilated area with the operator "upwind" from the container or provide ventilation to control airborne levels below the permissible exposure limit.
- NOTE: Passing vapors through activated carbon effectively removes Chloropicrin.
- Do not allow to spill.
- Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwaters or rinsate.
- Avoid contact with incompatible materials. See Section 10 for specific materials to avoid.
- Do not get in eyes, on skin, on clothing.



Tri-Clor Fumigant

- Always have adequate clean water available to wash the skin.
- If product splashes or spills on shoes or clothing, remove them at once. Vapors from contaminated area will be an intolerable source of irritation. If liquid contacts skin where rings or bandages are worn, remove them and wash exposed skin with soap and water. Air expose shoes or clothing outside and do not wear until free of all traces of fumigant. Keep and wash PPE and work clothing separately from other laundry. Discard clothing and other absorbent materials that have been drenched or heavily contaminated with this product.
- Keep away from heat, sparks, or open flame.
- Do not use water to clean equipment. Flush with nitrogen, compressed air, or solvent.
- Do not use containers or application equipment made of magnesium, aluminum, or their alloys, or alkali metals as under certain conditions, chloropicrin may be severely corrosive to such metals.
- Containers should never be refilled by the consumer or used for any other product or purpose.
- Use only dry nitrogen gas to pressurize cylinders. Polyethylene or Teflon[®] tubing may be used to transfer Chloropicrin at <u>low</u> pressures. Regulator must be operated with a <u>secondary</u> pressure relief valve. **DO NOT** use high pressure hose connection (such as stainless steel braided hose) between nitrogen cylinder and Chloropicrin cylinder.

CONDITIONS FOR SAFE STORAGE

- Cylinders and containers should be tightly closed and stored in a cool, dry, well-ventilated area under lock and key (secured).
- Keep flammable/combustible liquids, oxidizers, and combustible solid materials away from Chloropicrin containers.
- Store at temperatures not exceeding 55 °C (131 °F).
- Post as a pesticide storage area.
- Do not contaminate water, food, or feed by storage or disposal.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS FOR CHLOROPICRIN (CAS 76-06-2)

SOURCE OF EXPOSURE LIMIT	TYPE	VAL	.UE
US OSHA, Table Z-1 Limits for Air Contaminants, 29 CFR 1910.1000	TWA	0.1 ppm	0.7 mg/m^3
US ACGIH, Threshold Limit Values (TLVs)	TWA	0.1 ppm	0.67 mg/m^3
US NIOSH, Recommended Exposure Limits	TWA	0.1 ppm	0.7 mg/m^3
US NIOSH, Documentation for Immediately Dangerous to Life or	IDLH	2 ppm	
Health			

ENGINEERING CONTROLS

	Wash hands and face before breaks and immediately after handling product.
General Hygiene:	Handle in accordance with good industrial hygiene and safety practice.
	Use personal protective equipment as required.
	Keep working clothes separate.
	Provide easy access to adequate water supply for eye flushing or skin decontamination in
Equipment	the work area. For field handling and application situations, refer to the pesticide end-use
	label for emergency water requirements.
	For indoors, use process enclosures, local exhaust ventilation, or other engineering controls
Ventilation	to control airborne levels below recommended exposure limits. Lethal concentrations may
	exist in areas with poor ventilation.



Tri-Clor Fumigant

INDIVIDUAL PROTECTION MEASURES

Minimum Protection	INDIVIDUAL PI	ROTECTION MEASURES		
Protection * Long-sleeved shirt and long pants, and * Shoes and socks When performing tasks with potential for liquid contact, handlers and applicators must wear: Long-sleeved shirt and long pants, and Chemical-resistant gloves Butyl, Nitrile, or Neoprene are acceptable for incidental contact (<10 minutes) Chemical-resistant apron Saranex, neoprene, or chlorinated polyethylene provide short-term contact or splash protection against liquid product Protective eyewear as follows: Safety glasses with front, brow, and temple protection, or Face shield, or Faces shield, or Full-facepiece respirator NOTE: Eye goggles are NOT to be worn Chemical-resistant footwear with socks Longer-term protection is provided by PPE constructed of Viton, Teflon, and EVAL barrier laminates (for example, responder suits manufactured by Life-guard or Silvershield gloves manufactured by North). For more options, refer to the EPA Label Review Manual, EPA Chemical Resistance Category Selection Chart, Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product label's Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers sections, handlers must wear at a minimum either: **A NOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval number prefix TC-34A), or **A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). **For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: **A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. **IMPORTANT: An SCBA is not permitted for routine	Minimum	When performing tasks with NO potential for liquid contact, handlers and applicators must wear:		
When performing tasks with potential for liquid contact, handlers and applicators must wear: Long-sleeved shirt and long pants, and Chemical-resistant gloves Butyl, Nitrile, or Neoprene are acceptable for incidental contact (<10 minutes) Chemical-resistant apron Saranex, neoprene, or chlorinated polyethylene provide short-term contact or splash protection against liquid product Protective eyewear as follows: Safety glasses with front, brow, and temple protection, or Face shield, or Face shield, or Full-facepiece respirator NOTE: Eye goggles are NOT to be worn Chemical-resistant footwear with socks Longer-term protection is provided by PPE constructed of Viton, Teflon, and EVAL barrier laminates (for example, responder suits manufactured by Life-guard or Silvershield gloves manufactured by North). For more options, refer to the EPA Label Review Manual, EPA Chemical Resistance Category Selection Chart, Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product, or when taking air samples, or when an air-purifying respirator is required under this product label's Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers sections, handlers must wear at a minimum either: A NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval number prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-24A), or A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency when corrective action is needed to reduce air concentrat				
 Long-sleeved shirt and long pants, and Chemical-resistant gloves Butyl, Nitrile, or Neoprene are acceptable for incidental contact (<10 minutes) Chemical-resistant apron Saranex, neoprene, or chlorinated polyethylene provide short-term contact or splash protection against liquid product Protective eyewear as follows: 	1 1010011011	Shoes and socks		
Chemical-resistant gloves Butyl, Nitrile, or Neoprene are acceptable for incidental contact (<10 minutes) Chemical-resistant apron Saranex, neoprene, or chlorinated polyethylene provide short-term contact or splash protection against liquid product Protective eyewear as follows: Safety glasses with front, brow, and temple protection, or Face shield, or Full-facepiece respirator NOTE: Eye goggles are NOT to be worn Chemical-resistant footwear with socks Longer-term protection is provided by PPE constructed of Viton, Teflon, and EVAL barrier laminates (for example, responder suits manufactured by Life-guard or Silvershield gloves manufactured by North). For more options, refer to the EPA Label Review Manual, EPA Chemical Resistance Category Selection Chart. Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respiratory Protection and Stop Work Triggers sections, handlers must wear at a minimum either: **A NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval purples profuct C-24A), or A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Air concentration can be measured with a direct reading detection device, such as a Dräger,				
- Butyl, Nitrile, or Neoprene are acceptable for incidental contact (<10 minutes) • Chemical-resistant apron - Saranex, neoprene, or chlorinated polyethylene provide short-term contact or splash protection against liquid product • Protective eyewear as follows: - Safety glasses with front, brow, and temple protection, or - Face shield, or - Full-facepiece respirator - NOTE: Only NIOSH certified full facepiece air sust war at a minimum either: - A NIOSH certified full facepiece air approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval pumber prefix TC-24S) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval pumber prefix TC-24S) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-33C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-33C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-33C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-33C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-33C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-33C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-33C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-33C) cartridge and a particulate pre-filter (Type N, R, P, or H		Long-sleeved shirt and long pants, and		
Chemical-resistant apron Saranex, neoprene, or chlorinated polyethylene provide short-term contact or splash protection against liquid product Protective eyewear as follows: Safety glasses with front, brow, and temple protection, or Face shield, or Face shield, or Full-facepiece respirator NOTE: Eye goggles are NOT to be worn Chemical-resistant footwear with socks Longer-term protection is provided by PPE constructed of Viton, Teflon, and EVAL barrier laminates (for example, responder suits manufactured by Life-guard or Silvershield gloves manufactured by North). For more options, refer to the EPA Label Review Manual, EPA Chemical Resistance Category Selection Chart, Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product label's Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers sections, handlers must wear at a minimum either: **Respiratory** A NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval number prefix TC-32C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-43A), or A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. Meanutement Meanutement Air concentration can be measured with a direct reading detection device, such as a Dräger,		Chemical-resistant gloves		
- Saranex, neoprene, or chlorinated polyethylene provide short-term contact or splash protection against liquid product • Protective eyewera as follows: - Safety glasses with front, brow, and temple protection, or - Face shield, or - Full-facepiece respirator - NOTE: Eye goggles are NOT to be worn • Chemical-resistant footwear with socks Longer-term protection is provided by PPE constructed of Viton, Teflon, and EVAL barrier laminates (for example, responder suits manufactured by Life-guard or Silvershield gloves manufactured by North). For more options, refer to the EPA Label Review Manual, EPA Chemical Resistance Category Selection Chart, Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product, or when taking air samples, or when an air-purifying respirator is required under this product, or when taking air samples, or when an air-purifying respirator or a product label's Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers sections, handlers must wear at a minimum either: NOTE: Only NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval number prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter		- Butyl, Nitrile, or Neoprene are acceptable for incidental contact (<10 minutes)		
- Saranex, neoprene, or chlorinated polyethylene provide short-term contact or splash protection against liquid product • Protective eyewera as follows: - Safety glasses with front, brow, and temple protection, or - Face shield, or - Full-facepiece respirator - NOTE: Eye goggles are NOT to be worn • Chemical-resistant footwear with socks Longer-term protection is provided by PPE constructed of Viton, Teflon, and EVAL barrier laminates (for example, responder suits manufactured by Life-guard or Silvershield gloves manufactured by North). For more options, refer to the EPA Label Review Manual, EPA Chemical Resistance Category Selection Chart, Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product, or when taking air samples, or when an air-purifying respirator is required under this product, or when taking air samples, or when an air-purifying respirator or a product label's Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers sections, handlers must wear at a minimum either: NOTE: Only NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval number prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter		Chemical-resistant apron		
protection against liquid product Protective eyewear as follows: Safety glasses with front, brow, and temple protection, or Face shield, or Flace shield, or Flacepiace respirator Chemical-resistant footwear with socks Longer-term protection is provided by PPE constructed of Viton, Teflon, and EVAL barrier laminates (for example, responder suits manufactured by Life-guard or Silvershield gloves manufactured by North). For more options, refer to the EPA Label Review Manual, EPA Chemical Resistance Category Selection Chart, Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product label's Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers sections, handlers must wear at a minimum either: **A NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. Measurement Measurement Air concentration can be measured with a direct reading detection device, such as a Dräger,		<u> </u>		
Eyes, Face, Skin - Safety glasses with front, brow, and temple protection, or - Face shield, or - Full-facepiece respirator - NOTE: Eye goggles are NOT to be worn - Chemical-resistant footwear with socks Longer-term protection is provided by PPE constructed of Viton, Teflon, and EVAL barrier laminates (for example, responder suits manufactured by Life-guard or Silvershield gloves manufactured by North). For more options, refer to the EPA Label Review Manual, EPA Chemical Resistance Category Selection Chart, Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product label's Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers sections, handlers must wear at a minimum either: A NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Alicentered is a face of the protection device, such as a Dräger,		protection against liquid product		
Eyes, Face, Skin - Safety glasses with front, brow, and temple protection, or - Face shield, or - Full-facepiece respirator - NOTE: Eye goggles are NOT to be worn - Chemical-resistant footwear with socks Longer-term protection is provided by PPE constructed of Viton, Teflon, and EVAL barrier laminates (for example, responder suits manufactured by Life-guard or Silvershield gloves manufactured by North). For more options, refer to the EPA Label Review Manual, EPA Chemical Resistance Category Selection Chart, Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product label's Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers sections, handlers must wear at a minimum either: A NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Alicentered is a face of the protection device, such as a Dräger,				
Face shield, or Face shield, or Full-facepiece respirator NOTE: Eye goggles are NOT to be worn Chemical-resistant footwear with socks Longer-term protection is provided by PPE constructed of Viton, Teflon, and EVAL barrier laminates (for example, responder suits manufactured by Life-guard or Silvershield gloves manufactured by North). For more options, refer to the EPA Label Review Manual, EPA Chemical Resistance Category Selection Chart, Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product label's Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers sections, handlers must wear at a minimum either: **NOTE:**Only NIOSH** certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval number prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or **A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). **Portection** **A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. **IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. **Alternation** Air concentration can be measured with a direct reading detection device, such as a Dräger,**		▼		
- Full-facepiece respirator - NOTE: Eye goggles are NOT to be worn - Chemical-resistant footwear with socks Longer-term protection is provided by PPE constructed of Viton, Teflon, and EVAL barrier laminates (for example, responder suits manufactured by Life-guard or Silvershield gloves manufactured by North). For more options, refer to the EPA Label Review Manual, EPA Chemical Resistance Category Selection Chart, Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product, or when taking air samples, or when an air-purifying respirator is required under this product label's Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers sections, handlers must wear at a minimum either: **A NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or **A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). **For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: **A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Also concentration can be measured with a direct reading detection device, such as a Dräger,				
- NOTE: Éye goggles are NOT to be worn - Chemical-resistant footwear with socks Longer-term protection is provided by PPE constructed of Viton, Teflon, and EVAL barrier laminates (for example, responder suits manufactured by Life-guard or Silvershield gloves manufactured by North). For more options, refer to the EPA Label Review Manual, EPA Chemical Resistance Category Selection Chart, Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product, or when taking air samples, or when an air-purifying respirator is required under this product, or when taking air samples, or when an air-purifying respirator is required under this product label's Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers sections, handlers must wear at a minimum either: **Respiratory** ONOTE: Only NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant.		 Full-facepiece respirator 		
Chemical-resistant footwear with socks Longer-term protection is provided by PPE constructed of Viton, Teflon, and EVAL barrier laminates (for example, responder suits manufactured by Life-guard or Silvershield gloves manufactured by North). For more options, refer to the EPA Label Review Manual, EPA Chemical Resistance Category Selection Chart, Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product label's Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers sections, handlers must wear at a minimum either: A NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Air concentration can be measured with a direct reading detection device, such as a Dräger,	Skin			
laminates (for example, responder suits manufactured by Life-guard or Silvershield gloves manufactured by North). For more options, refer to the EPA Label Review Manual, EPA Chemical Resistance Category Selection Chart, Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product label's <i>Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers</i> sections, handlers must wear at a minimum either: **A NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or **A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). **For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: **A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. **Measurement** Air concentration can be measured with a direct reading detection device, such as a Dräger,				
laminates (for example, responder suits manufactured by Life-guard or Silvershield gloves manufactured by North). For more options, refer to the EPA Label Review Manual, EPA Chemical Resistance Category Selection Chart, Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product label's <i>Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers</i> sections, handlers must wear at a minimum either: **A NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or **A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). **For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: **A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. **Measurement** Air concentration can be measured with a direct reading detection device, such as a Dräger,				
manufactured by North). For more options, refer to the EPA Label Review Manual, EPA Chemical Resistance Category Selection Chart, Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product label's <i>Directions for Use, Protection for Handlers, Respiratory Protection and Stop</i> Work Triggers sections, handlers must wear at a minimum either: **OA NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or **A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC- 14G). **For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: **A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. **MOORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Air concentration can be measured with a direct reading detection device, such as a Dräger,				
Chemical Resistance Category Selection Chart, Category H. Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product label's <i>Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers</i> sections, handlers must wear at a minimum either: **NOTE:**Only NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or **A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: **A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Air concentration can be measured with a direct reading detection device, such as a Dräger,				
Where chemical-resistant materials are required, leather, canvas, or cotton materials offer no protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product label's <i>Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers</i> sections, handlers must wear at a minimum either: **NOTE:**Only NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or **A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: **A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Air concentration can be measured with a direct reading detection device, such as a Dräger,		<u>▼</u>		
protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product label's <i>Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers</i> sections, handlers must wear at a minimum either: **NOTE:* Only NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or **A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: **A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. **Air concentration can be measured with a direct reading detection device, such as a Dräger,*		Chemical Resistance Category Selection Chart, Category H.		
protection from this product and must not be worn as the sole article of protection when contact with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product label's <i>Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers</i> sections, handlers must wear at a minimum either: **NOTE:* Only NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or **A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: **A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. **Air concentration can be measured with a direct reading detection device, such as a Dräger,*		Where chemical-resistant materials are required leather, canvas, or cotton materials offer no		
with this product is possible. If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product label's <i>Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers</i> sections, handlers must wear at a minimum either: **NOTE:* Only NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or **A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). **For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: **A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. **Air concentration can be measured with a direct reading detection device, such as a Dräger,*		-		
If working in an environment where the eyes are stinging and watery due to exposure to this product, or when taking air samples, or when an air-purifying respirator is required under this product label's <i>Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers</i> sections, handlers must wear at a minimum either: **NOTE:** Only NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or **A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). **For emergency response, wear a self-contained breathing apparatus (SCBA) as follows:* **A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes.** IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. **Maccurrent**				
product, or when taking air samples, or when an air-purifying respirator is required under this product label's <i>Directions for Use</i> , <i>Protection for Handlers</i> , <i>Respiratory Protection and Stop Work Triggers</i> sections, handlers must wear at a minimum either: • A NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or • A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: • A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Maccourage of the product of				
product label's <i>Directions for Use, Protection for Handlers, Respiratory Protection and Stop Work Triggers</i> sections, handlers must wear at a minimum either: • A NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or • A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: • A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Macausement Air concentration can be measured with a direct reading detection device, such as a Dräger,				
Respiratory A NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Macausement Air concentration can be measured with a direct reading detection device, such as a Dräger,				
A NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Measurement Air concentration can be measured with a direct reading detection device, such as a Dräger,				
(OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or • A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: • A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Maccurement Maccurement				
(OV, NIOSH approval prefix TC-23C) cartridge and a particulate pre-filter (Type N, R, P, or HE, NIOSH approval number prefix TC-84A), or • A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: • A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Maccurement Maccurement	Respiratory	A NIOSH certified full facepiece air-purifying respirator equipped with an organic vapor		
or HE, NIOSH approval number prefix TC-84A), or • A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: • A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Magaziroment Air concentration can be measured with a direct reading detection device, such as a Dräger,				
 A gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G). For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Air concentration can be measured with a direct reading detection device, such as a Dräger, 				
NOTE: Only NIOSH certified respirators may be used for Respiratory Protection For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: • A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Macausement Air concentration can be measured with a direct reading detection device, such as a Dräger,				
For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: • A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Macausement Air concentration can be measured with a direct reading detection device, such as a Dräger,				
For emergency response, wear a self-contained breathing apparatus (SCBA) as follows: • A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Magnetic ment as the formula of the property of the proper	,			
A full facepiece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Measurement Air concentration can be measured with a direct reading detection device, such as a Dräger,	respirators may	For emergency response, wear a self-contained breathing apparatus (SCBA) as follows:		
thirty minutes. IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Magnuscent Air concentration can be measured with a direct reading detection device, such as a Dräger,		7 2		
IMPORTANT: An SCBA is not permitted for routine handler tasks. If responding to an emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Magnuscent Air concentration can be measured with a direct reading detection device, such as a Dräger,	, ,	• •		
emergency when corrective action is needed to reduce air concentrations to acceptable levels, wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Air concentration can be measured with a direct reading detection device, such as a Dräger,				
wear an SCBA. Escape-only SCBA respirators must not be used by handlers for responding to emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Air concentration can be measured with a direct reading detection device, such as a Dräger,				
emergencies. In addition, wear PPE required for potential contact with liquid fumigant. Air concentration can be measured with a direct reading detection device, such as a Dräger,				
Air concentration can be measured with a direct reading detection device, such as a Dräger,				
		emergencies. In addition, wear PPE required for potential contact with liquid fumigant.		
Sensidyne or Kitigawa pump, using its Chloropicrin detector tube.	Magairamant			
	ivicasui ei i i ei i l	Sensidyne or Kitigawa pump, using its Chloropicrin detector tube.		



Tri-Clor Fumigant

PERSONAL PROTECTION FOR SPILLS/EMERGENCY

Fire	If fire only, use normal fire-fighting equipment. If chemical releases and fire involved, wear recommended chemical protective clothing in conjunction with fire-fighting gear.			
Spills	Minimum PPE: Full facepiece air-purifying respirator with organic vapor cartridge and chemical resistant gloves. Upgrade respiratory protection in accordance with the "Respiratory" section above.			
Chemical Protective Clothing	 For small cleanup where liquid splash is unlikely, loose-fitting or well ventilated long-sleeved shirt, long pants or coveralls, socks with shoes may be worn. If contact occurs, remove contaminated clothing immediately to prevent skin irritation or burn. For cleanup where liquid splash is likely, a liquid impervious chemical coverall with booties and head cover may be worn, for example, Tyvek® QC or Saranex™ SL. In confined areas or areas where substantial vapor levels exist, wear a vapor-tight suit made of a material such as Tychem® TK or Kappler CPF 3. Use a Dupont™ Responder® level suit or equivalent for use against permeation by Chloropicrin for periods greater than 8 hours. Teflon® withstands permeation from 4 to 8 hours. 			

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear colorless liquid in normal storage. Pale vallow if aged or exposed to air			
Appearance	Clear, colorless liquid in normal storage. Pale yellow if aged or exposed to air.			
Odor	Strong, sharp, irritating (pungent). Chloropicrin is readily identifiable by smell.			
Odor Threshold	700 ppb in 2-5 seconds			
рН	Not applicable			
Melting Point	-69.2 °C (-92.56 °F)			
Freezing Point	-69.2 °C (-92.56 °F)			
Boiling Point	112 °C (233.6 °F) (757 mm Hg, 100.925kPa)			
Boiling Range	Not available			
Flash Point (°C)	No flash point determined below 100 °C (212 °F)			
Flammability (solid, gas)	Not flammable			
Flammability Limits in air,	Not applicable			
Upper % by volume	Not applicable			
Flammability Limits in air,	Not applicable			
Lower % by volume	Not applicable			
Autoignition Temperature	No ignition occurred when tested up to 402 °C (755 °F)			
Evenoration Data	Fast 0.00017 lbs/sec/ft ² at 15.5 °C (60 °F) and 13.7 km/h (8.5 mph) wind			
Evaporation Rate	0.00008 lbs/sec/ft ² at 15.5 °C (60 °F) and 5.3 km/h (3.3 mph) wind			
	18.3 mm Hg @ 20 °C (68 °F) Volatile			
Vapor Pressure	2.2610 kPa @ 20 °C			
	5.77 mmHg @ 0 °C, 79 mmHg @ 50 °C			
Vapor Density	5.7 (air = 1)			
Relative Density (g/cm ³)	1.6558 @ 20 °C (68 °F) H ₂ O = 1			
(Specific Gravity)	1.69225 @ 0 °C			
Density @ 20 °C	13.88 lbs/gal			



Tri-Clor Fumigant

Solubility	Slightly in water. 0.16 grams/100 ml (0.016%) in water, 1.6 g/L			
Partition Coefficient (n-octanol/water)	Soluble in acetonitrile, hydrocarbon solvents 2.38 log K _{ow}			
Decomposition	127 °C (261 °F)			
Temperature	At its boiling point, chloropicrin slowly decomposes			
Viscosity	0.73 centistokes @ 20 °C			
% Volatile	100			
Molecular Formula	CCl ₃ NO ₂			
Molecular Weight	164.37			
Critical Pressure	640 psia			
Critical Temperature	145 °C (293 °F)			
Saturated Vapor Density	0.0068 gm/cc @ 20 °C/Air=1			
Liquid Surface Tension	$32.3 \text{ dynes/cm} = 0.0323 \text{ N/m} \text{ at } 20 ^{\circ}\text{C}$ (not considered to be surface active) 71.0mN m^{-1}			
Ratio of Specific Heats of Vapor (Gas)	1.0991			
Latent Heat of Vaporization	103 Btu/lb = 57.3 cal/g = 2.4 X 105 J/kg			
Heat of Fusion	48.16 cal/g			
Henry's Law Constant	43.84 Pa.m ³ .mol ⁻¹ Moderately volatile (2.15 E-03 atm-M3 mole (estimated)			

Conversion

To convert inhalation results for Chloropicrin:

10. STABILITY AND REACTIVITY

Reactivity	 Hazardous polymerization is not known to occur. Cylinders containing chloropicrin can rupture or burst when subjected to fire or temperatures above 60 °C (140 °F). 			
Chemical Stability	Product is stable under normal temperatures and pressures.			
Possibility of Hazardous Reactions	If heated under confinement, may develop accelerated decomposition.			
Conditions to Avoid	 Contamination with water can lead to the generation of corrosive constituents over time. Unstable under fire conditions. Avoid temperatures above 60 °C (140 °F). 			
Incompatible Materials	 Do not use with aluminum and its alloys, organic amines, aniline in presence of heat, sodium methoxide, magnesium and its alloys, or alkali metals. Degrades PVC, dissolves rubber compounds and fiberglass resin, and is mildly 			
Hazardous	 corrosive to carbon steel in presence of moisture. Phosgene, hydrogen chloride, carbon monoxide, chlorine, nitrosyl chloride, and 			
Decomposition Products • Phosgene, hydrogen chloride, carbon monoxide, chlorine, hitrosyl chloride, carbon monoxide, chloride, carbon monoxide, chloride, carbon monoxide, chloride, chloride, carbon monoxide, chloride, chloride, carbon monoxide, chloride, chlori				
Explodability	Did not exhibit heat or shock sensitivity when tested per EEC Method A14.			



Tri-Clor Fumigant

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure:	 Eyes (mainly due to vapors in air) Respiratory Tract (by inhalation of vapors) Skin (mainly by contact with liquid) Ingestion
Signs & Symptoms of Exposure	Vapor Contact: Eye irritation, stinging, tearing at low concentrations Throat irritation, coughing Dripping nasal mucous Nausea, vomiting, abdominal pain, headache Dizziness, drowsiness, unconsciousness Breathing difficulty, cyanosis (bluish looking skin/lips) Pulmonary edema, and death due to pulmonary edema Liquid Contact: Skin blistering Skin, eye, and portal tissue burns

SHORT TERM (ACUTE, IMMEDIATE) OR DELAYED EFFECTS:

Inhalation	 At 73-150 ppb, chloropicrin behaves as a mild sensory irritant. Above 150 ppb, cough, headache, nausea, and vomiting may occur. These symptoms are temporary and reversible following termination of exposure. At levels above 300 ppb, respiratory symptoms may increase in severity and include difficulty in breathing. At levels above 580 ppb for 8 hours or 2000 ppb for 10 minutes, life-threatening effects including pulmonary edema (fluid in lungs) can occur. Severe pulmonary responses can be delayed following onset of exposure.
Eyes	 Exposure to vapor concentrations from 73-150 ppb can produce mild eye irritation or tearing but stops following termination of exposure. Exposure to higher concentrations will produce an increase in severity and earlier onset of irritation and tearing. Vision may be temporarily impaired. Direct contact with liquid chloropicrin can cause burns to the eyes and produce permanent damage.
Skin	 Direct contact with liquid chloropicrin can cause irritation, blistering, or burns. Burns can produce permanent damage to the skin. Prolonged or widespread skin contact may result in absorption of amounts which could cause death.
Ingestion	Ingestion of liquid chloropicrin can cause burns to and produce permanent damage to the mouth, throat, esophagus and stomach. Ingestion of large quantities of chloropicrin liquid can be fatal.
Specific Organ Toxicity	Respiratory system, lungs



Tri-Clor Fumigant

Chronic Effects	Long-term overexposure to inhalation of chloropicrin could result in inflammatory damage to the respiratory tract.			
Specific Target Organ Toxicity	Repeated-Dose Toxicity: Subchronic inhalations studies in mice and rats established that respiratory tissue is the target for chloropicrin inhalation toxicity and that portal-of-entry effects occur in the upper respiratory tissue of animals inhaling chloropicrin vapor for 90 days at concentrations at or above 0.1ppm (0.67mg/m³).			
	Long-term Toxicity: Chronic inhalation studies in mice and rats established that the respiratory tissue is the target for chloropicrin inhalation toxicity and that tissue of the entire respiratory is subject to inflammatory damage. The NOAEL for respiratory system changes in chronic inhalation bioassays is 0.1 ppm for rats and mice.			
Respiratory or Skin Sensitization	Data not available			
Carcinogenicity	Not Listed: IARC - International Agency for Research on Cancer Not Listed: NTP - National Toxicology Program Not Listed: OSHA - US Occupational Safety and Health Administration			
	ACGIH A4 – Not classifiable as a human carcinogen			
	At least six long-term bioassays have been completed with chloropicrin to evaluate the potential of this compound to cause chronic and/or carcinogenic effects. Neoplasms were not seen in chloropicrin-treated animals at an incidence greater than concurrent or historic control animals.			
Mutagenicity	In vitro studies produced mixed and contradictory results for genetic toxicity and mutation. In vivo studies are negative for mutation, DNA damage and chromosome damage.			
Reproductive Toxicity	Inhalation exposure to chloropicrin of male and female rats in a 2-generation reproductive function study produced an NOAEL of 1.0ppm for systemic toxicity and greater than 1.5ppm for developmental toxicity and reproductive parameters. These data indicate that reproduction fitness is not adversely affected by chloropicrin inhalation even at systemically toxic levels.			
Developmental Toxicity	Developmental toxicity studies in rats and rabbits conducted by the inhalation route of exposure showed that the NOAEL for maternal toxicity in rats was 0.4ppm and 1.2ppm for fetal toxicity. In rabbits NOAEL for maternal toxicity was 0.4ppm and 1.2ppm for fetal toxicity indicating that the developing fetus is not a target tissue for chloropicrin toxicity.			
Neurotoxicity	Data not available			
Aspiration Hazard	Data not available			
Interactive Effects	Data not available			
Confirmation of exposure	There is no biological indicator for exposure to Chloropicrin.			



Tri-Clor Fumigant

HUMAN AND ANIMAL TOXICOLOGY STUDIES:

73 ppb	Human sensory irritation threshold (eye irritation).		
73 ppb to 150 ppb	Human response - mild irritant to eyes and throat.		
> 150 ppb	Human response - headache, nausea, and vomiting may occur. These symptoms are temporary and reversible following termination of exposure.		
> 300 ppb	Human response - respiratory symptoms may increase in severity and include difficulty in breathing.		
> 580 ppb (8 hrs) or 2000 ppb (10 minutes)	Human response - life-threatening effects including pulmonary edema can occur.		
18.9 ppm (126.6 mg/m ³)	Acute Inhalation LC_{50} Rat: 4 Hour (for both sexes with 95% confidence limits of 16.5 to 21.6 ppm (110.6 - 144.7 mg/m ³)		
2.34 ppm (15.7 mg/m ³)	Acute Inhalation RD $_{50}$ mice: with 95% confidence limits of 1.84 to 2.58 ppm ($12.2-17.3~\text{mg/m}^3$)		
37.5 mg/kg	Acute Oral LD ₅₀ Rat		

12. ECOLOGICAL INFORMATION

Ecotoxicity	Toxic to aquatic life			
Aquatic Toxicity	 Toxic to aquatic life Daphnia: EC₅₀ = 120 μg/L, 48 Hr, acute Mysid: EC₅₀ = 40 μg/L, 96 Hr Sheepshead Minnow: EC₅₀ = 100 μg/L; 96 Hr Trout: EC₅₀ = 11 μg/L; 96 Hr Bluegill/Sunfish: EC₅₀ = 50 μg/L; 96 Hr Eastern Oyster: EC₅₀=6.4μg/L, 96 Hr Aquatic plant growth (Lemna): NOEC=11μg/L, 7 day 			
Terrestrial Toxicity	 Aquate plaint growth (Lehnia). NOEC=11μg/L, 7 day Honeybee dermal LD₅₀ > 100 μg/L, 48 Hr Acute avian inhalation NOEC = 96 ppb, 4 hours per day for 5 days Terrestrial seedling emergence and vegetative vigor NOEC = 100 μg/L air. Exposure 6 hours per day for two days. 			
Persistence and Biodegradability (Environmental Fate)	 Atmospheric half-life estimated to be 1 day. Initial photolysis products include phosgene and nitrosyl chloride and chlorine; subsequently nitrogen dioxide and dinitrogen tetraoxide. Aquatic photolysis half-life = 1.3 days Aerobic soil metabolism half-life = 4.5-10 days; major degradate is carbon dioxide. Evaporation half- life of chloropicrin in water (light) = 4.8- 9.4 minutes; (dark) 4.1-15.7 minutes). 			
Bioaccumulative Potential	Due to low log Po/w (<5.0) chloropicrin is not expected to bioaccumulate			
Mobility in Soil	Data not available			
Other Adverse Effects (i.e. ozone)	Data not available			
Partition Coefficient (n-octanol/water)	2.38 log K _{ow}			



Tri-Clor Fumigant

13. DISPOSAL CONSIDERATIONS

Cylinder Management	 Cylinders should be returned according to instructions on the cylinder. Close the valve when the cylinder is empty and install the safety cap(s) and bonnet. Do not ship cylinders without safety caps or valve protection bonnets. When a cylinder is partially full and there is no further requirement for the product, contact the distributor for return instructions. 			
Railcar Management	 An extra seal is provided in the railcar dome to be used when returning the railcar. Contact the distributor for specific return instructions, if necessary. 			
Safe Handling	 Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a national pollutant discharge elimination system (NPDES) permit. Do not discharge effluent containing this product to sewer systems. 			
Refillable Container	 Only the registrant or distributor is allowed to refill pesticide into containers. Do not reuse this container for any other purpose. 			
Railcar Management	 An extra seal is provided in the railcar dome and is to be used when returning the railcar. Contact the distributor for specific return instructions, if necessary. 			
Safe Handling	 Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a national pollutant discharge elimination system (NPDES) permit. Do not discharge effluent containing this product to sewer systems. 			
Disposal of Product	 Do not contaminate water, food, or feed by storage or disposal. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, the Hazardous Waste representative at the nearest EPA Regional Office, or the product manufacturer or distributor for guidance. 			
 Container Disposal Container Disposal Container Disposal Container Disposal To clean the container before final disposal, remove any remaining liquid, using air pressure if necessary. Allow container to aerate for at least 5 days. After aeration, wash container using hot water; then offer container to qualified reconditioner or dispose of as directed by State or local regulations. 				

14. TRANSPORT INFORMATION

US DOT, TDG, IMDG

UN Number	UN1580
Proper Shipping Name	Chloropicrin
Transport Hazard Class(es)	6.1
Packing Group	I
Toxic-Inhalation Hazard	Yes
Hazard Zone	В
Environmental Hazards	Aquatic



Tri-Clor Fumigant

Marine Pollutant	Yes		
Hazardous Substance	No Reportable Quantity (RQ) listed for Chloropicrin		
Transport in Bulk per MARPOL	Not applicable		
Labels/Placards	US DOT: Class 6.1, Poison Inhalation Hazard		
Labels/Flacalus	IMDG, TDG, ADR, United Nations: Class 6.1, Toxic Substances		
Air Transport (IATA/ICAO)	Forbidden for any amount		
Emergency Guide	154 (NAERG – North American Emergency Response Guide)		
IMDG EmS	F-A, S-A (General Fire Schedule, Spillage Schedule Toxic Substances)		
	Packages must be secured against all movement during transport. Keep		
Special Precautions	markings, labels or placards on package until cleaned and purged of residue		
	including bulk and non-bulk packages. For cylinders, ensure valve is closed		
	and safety cap(s) and valve protection are in place prior to transport.		

15. REGULATORY INFORMATION

U.S FEDERAL

OSHA This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

DEA Drug Enforcement Administration – 21 CFR 1308.11-15 – Not controlled.

CWC Chemical Weapons Convention – Chloropicrin is listed as a Schedule 3 substance subject to

declaration and reporting.

FIFRA

This chemical is a pesticide product registered by the U.S. Environmental Protection Agency and is subject to certain labeling requirements under US federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label.

POISON DANGER

Chloropicrin fumigant has the capacity to cause marked irritation to the upper respiratory tract, and is a strong lachrymator (tear producing eye irritant). Low concentrations, below those necessary to cause serious systemic intoxication, are capable of causing severely painful eye irritation, hence will not be voluntarily tolerated. However, the effect may be so powerful that a person may become temporarily blinded and panic-stricken and that in turn may lead to accidents.

- Poisonous liquid and vapor.
- Inhalation may be fatal.
- Chloropicrin is readily identifiable by smell.
- Exposure to very low concentrations of vapor will cause irritation of eyes, nose, and throat.
- Continued exposure after irritation, or higher concentrations may cause painful irritation to the eyes or temporary blindness.
- Liquid will cause chemical burns to skin or eyes.
- Do not get on skin, in eyes, or on clothing.
- Harmful or fatal if swallowed.
- This product is toxic to mammals, birds, fish, and aquatic invertebrates.
- This product may be corrosive under certain conditions.

TriCal INC.

SAFETY DATA SHEET

Tri-Clor Fumigant

- Chloropicrin has certain properties and characteristics in common with chemicals that have been detected in groundwater (chloropicrin is highly soluble in water and has low adsorption to soil).
- For untarped applications of chloropicrin, leaching and runoff may occur if there is heavy rainfall after soil fumigation.

This fumigant is a highly hazardous material and must be handled with care only by certified applicators or persons under their direct supervision who are trained with its proper use. Consult your dealer representative or the distributor for correct procedure before using. Read and follow all label directions and product literature specific to your requirements.

CERCLA - Superfund): (SARA Title III)

Section 302.4 (RQ)	Chloropicrin is not listed with an RQ (Reportable Quantity)				
Section 302, EHS (TPQ)	Chloropicrin does not have a TPQ (Threshold Planning Quantity)				
Section 311/312 (Tier II)	Yes				
SARA Hazard Codes	Chloropicrin, CAS# 76-06-2 Immediate Hazard - Yes				
Section 313	This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of EPCRA section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372):				
	CAS Registry Number	Chemical Name	% by Weight		
	76-06-2	Chloropicrin	99.0%+		

RCRA - Resource Conservation and Recovery Act - Hazardous Wastes

	Chloropicrin is not specifically listed; however, prior to disposal of waste
Listed U or P	Chloropicrin or Chloropicrin-contaminated materials, the generator will need to
	evaluate if its waste characteristics are hazardous or non-hazardous.

TSCA - Toxic Substances Control Act

TSCA Inventory List, Section 8(b):	Chloropicrin, CAS# 76-06-2 is listed
Health & Safety Reporting List, Section 8(d)	Not listed
Chemical Test Rules, Section 4	Not listed under these rules
Export Notification, Section 12b	Not listed under this section
TSCA Significant New Use Rule, Section 5(a)	Not listed under this rule

Clean Air Act

Hazardous Air Pollutants	Not listed
Class 1 or 2 Ozone depletors	Not listed

Clean Water Act / Oil Pollution Act of 1990

Section 311	Not listed
Hazardous Substances	Not listed
Priority Pollutants	Not listed
Toxic Pollutants	Not listed

STATE

Chloropicrin can be found on the following state right-to-know lists:

California, New Jersey (Reportable threshold 500 lbs), Florida, Pennsylvania, Minnesota, Massachusetts
California Proposition 65 – Not listed.



Tri-Clor Fumigant

16. OTHER INFORMATION

Hazard Rating Systems`

	NFPA 704*	ACA-HMIS**
Category	Chloropicrin	Chloropicrin
Health	4	4
Flammability	0	0
Reactivity	3	3

Hazard Key		
4	-	Severe
3	-	Serious
2	-	Moderate
1	-	Slight
0	-	Minimal

 $^{*\} NFPA\ 704-Standard\ System\ for\ the\ Identification\ of\ the\ Hazards\ of\ Materials\ for\ Emergency\ Response$

ABBREVIATIONS:

ACGIH	American Conference of Governmental Industrial Hygienists		
ADR	European Agreement concerning the Internal Carriage of Dangerous Goods by Road		
CAS	Chemical Abstracts Service		
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act		
CFR	Code of Federal Regulations		
CHEMTREC	Chemical Transportation Emergency Center		
DOT	Department of Transportation (USA)		
	Half Maximal Effective Concentration - concentration of a material in water, a single dose		
EC ₅₀	which is expected to cause a biological effect on 50% of a group of test species.		
EPCRA			
	Immediately Dangerous to Life and Health - the maximum airborne concentration from		
IDLH	which one could escape [within 30 minutes] without any escape-impairing symptoms or		
	any irreversible health effects.		
IMDG	International Maritime Dangerous Goods		
LC ₅₀	Lethal Concentration - median dose at which 50% of test animals die from inhalation		
LD_{50}	Lethal Dose - median dose at which 50% test animals die from oral or dermal exposure		
NFPA	National Fire Protection Association		
NOAEL	No Observable Adverse Effect Level		
NOEC	No Observed Effect Concentration		
NTP	Normal Temperature and Pressure: 20 °C and 760 mmHg or 68 °F and 1 atm		
OSHA	Occupational Health and Safety Administration		
ppb	part per billion		
ppm	part per million		
PPE	Personal Protective Equipment		
RD_{50}	Respiratory Distress in 50% of test animals		
SARA	US EPA Superfund Amendments and Reauthorization Act		
STEL	Short Term Exposure Limit Workers can be exposed to a maximum of four STEL periods		
SIEL	per 8 hour shift, with at least 60 minutes between exposure periods.		
STP	Standard Temperature and Pressure: 0 °C and 760 mmHg or 32 °F and 1 atm		
TDG	Transport of Dangerous Goods (Canada)		
TWA	Time Weighted Average airborne concentration for a worker in an 8 hour day		
US DOT	United States Department of Transportation		
	Page 16 of 17		

^{**} ACA - HMIS – American Coatings Association - Hazardous Material Information System



SAFETY DATA SHEET Tri-Clor Fumigant

REVISION DATE: February 19, 2015

VERSION NO:

SDS NUMBER: 100-USA-TCI

Revision 10-18-13

Section 7 – Removed nitrogen pressure reference

Section 9 – Corrected decomposition temperature

Section 10 – Revised Possibility of Hazardous Reactions

Section 10 – Added Explodability section and information

Revision 11-15-14

Section 2 – Relocated Hazards Not Otherwise Specified and added information

Revision 02-19-15

Removed blank page

Section 1 – Added email address

WARRANTY

Notice: The information above is believed to be accurate and represents the best information currently available to us. Seller warrants that this product conforms to its chemical description and is reasonably fit for the purposes stated on the label when used in accordance with directions under normal conditions of use, but neither this warranty nor any other warranty of merchantability or fitness for a particular purpose, express or implied, extends to the use of this product contrary to label instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to seller, and buyer assumes the risk of any such use. In no way shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential, or exemplary damages, howsoever arising, even if the company has been advised of the possibility of such damages.